

Main applications

High-end and large roofs
Stadium roofs
Sport hall covers



Superior Service Life and Aesthetics

Long term service life and durable aesthetics for demanding translucent roofs

Major advantages

- Proven design life >30 years
- Durably clean & easy maintenance
- High translucency & consistent colour (VISU)
- High dimensional stability due to Precontraint® technology

Other applications

- Shading structures
- Awning & walkway covers

Technical specifications

Flexlight

	Xtrem TX30-II	Xtrem TX30-III	Xtrem TX30-IV	Xtrem TX30-V
Base fabric	Anticapilarity low wick yarn treatment			
Weight - EN ISO 2286-2	1050 g/m ²	1050 g/m ²	1350 g/m ²	1500 g/m ²
Standard format length	250 lm	250 lm	250 lm	200 lm
Tensile strength (warp/weft) EN ISO 1421	430/430 daN/5 cm	560/560 daN/5 cm	800/700 daN/5 cm	1000/800 daN/5 cm
Tear strength (warp/weft) DIN 53.363	55/50 daN	80/65 daN	120/110 daN	160/140 daN
Flame retardancy	B-s2, d0	C-s2, d0	C-s2, d0	C-s2, d0
Warranty*	20 years	20 years	20 years	20 years
MOQ**	2500 lm			
Maximum delivery time	4 working weeks			
Provided services	Special colours (limited) Promised delivery guaranteed up to 2 000 lm			

HANDLING & FABRICATION PRECAUTIONS:

TX30 shall be abraded before welding. Please refer to the TX30 handling and fabrication recommendations.

* Please refer to the text of our warranty. The warranty is valid only after confirmation on a case-by-case basis of warranty application. The warranty will not apply to mobile structures. The buyer of our products is fully responsible for their application or their transformation concerning any possible third party. The buyer of our products is responsible for their implementation and installation according to the standards, use and customs and safety rules of the countries where they are used.

**This MOQ is for the category custom made products. (Category C)